



# Tank containers

	1 chamber	3–4 chambers
<b>Container type</b>	• ISO, BIN, SWAP	—
<b>Frame length</b>	• 6,058 m–7,82 m	• 7,15 m–7,82 m
<b>Capacity</b>	• 16–35 m <sup>3</sup>	• 27–32 m <sup>3</sup>
<b>Features</b>	<ul style="list-style-type: none"> <li>• steam or water-glycol heating</li> <li>• with optional riser</li> <li>• with optional wash plates</li> <li>• ADR and IMO approval</li> </ul>	<ul style="list-style-type: none"> <li>• steam or water-glycol heating</li> <li>• ADR and IMO approval</li> </ul>
<b>Insulation</b>	• max 150 mm	• 90 mm–100 mm
<b>Tank material</b>	• V4A (coatings on request)	• V4A (coatings on request)
<b>Applications</b>	<ul style="list-style-type: none"> <li>• harmless chemicals</li> <li>• Class 3, 6.1, 8, and 9 chemicals</li> <li>• MDI/TDI</li> <li>• foodstuffs (single trip)</li> </ul>	<ul style="list-style-type: none"> <li>• harmless chemicals</li> <li>• Class 3, 6.1, 8, and 9 chemicals</li> <li>• MDI/TDI</li> <li>• foodstuffs (single trip)</li> </ul>

# Road tankers

	1–4 chambers
<b>Capacity</b>	• 24–54 m <sup>3</sup>
<b>Features</b>	<ul style="list-style-type: none"> <li>• some models with electric</li> <li>• glycol heating</li> <li>• steam heating</li> <li>• ADR approval</li> <li>• some models with threshold indicator</li> <li>• some models with dead man's handle</li> <li>• some models with silica gel filter</li> </ul>
<b>Insulation</b>	• max 200 mm
<b>Tank material</b>	• V4A
<b>Applications</b>	<ul style="list-style-type: none"> <li>• harmless chemicals</li> <li>• Class 3, 6.1, 8, and 9 chemicals</li> </ul>

# Gas tank containers

	20'	30' (1 chamber)
<b>Capacity</b>		• 32–42 m <sup>3</sup>
<b>Features</b>	<ul style="list-style-type: none"> <li>• 20' gas tank containers are available for diverse gases</li> </ul>	<ul style="list-style-type: none"> <li>• misc connections TODO/flange/ACME, etc.</li> <li>• hydraulische Bodenventilbetätigung</li> <li>• ADR and IMO approval</li> </ul>
<b>Insulation</b>		• max 100 mm
<b>Tank material</b>		• structural/stainless steel
<b>Applications</b>		<ul style="list-style-type: none"> <li>• isobutene</li> <li>• butadiene</li> <li>• MMA/TMA</li> <li>• dimethyl ether (DME)</li> <li>• ethylene oxide (EOX)</li> <li>• propylene oxide (propox) (Cl. 3)</li> <li>• etc.</li> </ul>

All products are tested for tank compatibility.

# Silo containers

	30'
<b>Capacity</b>	• 47 m <sup>3</sup>
<b>Features</b>	<ul style="list-style-type: none"> <li>• 2.0 bar working pressure</li> <li>• ADR approval</li> </ul>
<b>Tank material</b>	• ALMg 4,5 Mn
<b>Applications</b>	• free flowing products

